

PRODUCTS

RECOMMENDED APPLICATION AREAS

PRODUCT NAME	TRIPOLYMER ROOFING SEALANT	MS HYBRID ROOFING SEALANT	MS HYBRID ROOFING SEALANT (CLEAR)	POLYURETHANE ROOFING SEALANT	FAST-SKIN POLYURETHANE ROOFING SEALANT	SOLVENT-BASED BRUSHABLE ROOF REPAIR SEALANT	WET-DRY ROOF CEMENT
COLOR/ PART NUMBER/ SALES NUMBER	CLEAR: KST058450-01 650433121 & KST058451-GO 650433188 WHITE: KST058400-01 650433196 & KST058401-GO 650442635 BLACK: KST058410-01 650433212 & KST058411-GO 650433220	WHITE: KST058300-01 650433089 BLACK: KST058310-01 650433097	CLEAR KST058350-01 650433105	WHITE: KST058100-01 650432925 BLACK: KST058110-01 650436256 GRAY: KST058120-01 650432982	WHITE: KST058200-01 650433006 BLACK: KST058210-01 650433022	CLEAR: KST058550-16 650433253 WHITE: KST058500-16 650433261 BLACK: KST058510-16 650433279	BLACK KST058600-01 650441769 KST058600-16 650442643 KST058600-30 650442692 KST058600-20 650442684
FILL LEVEL	10.3 FL.oz 29 FL.oz	10.1 FL.oz	9.5 FL.oz	10.1 FL.oz	10.1 FL.oz	1 Gallon	10 FL.oz 1 Gallon 3 Gallon 5 Gallon
FLASHING	✓	✓	✓	✓	✓	✓	✓
GUTTERS	✓	✓	✓			✓	✓
LEAK REPAIR	✓	✓	✓			✓	✓
ROOF PENETRATIONS	✓	✓	✓	✓	✓		✓
SCREW HEADS	✓					✓	
SKYLIGHT FRAMES	✓	✓	✓				
TERMINATION POINTS	✓	✓	✓	✓	✓		
EPDM LAP SEAL		✓					
EPDM SCRIM EDGE SEAL		✓					
PARAPET CAPS/WALLS	✓	✓	✓	✓	✓	✓	
PITCH PANS		✓					
SEAL HOLES	✓	✓	✓			✓	✓
REPAIR TEARS		✓	✓			✓	✓

UNIGUARD™ Warranty Program

Making an investment in roof restoration is an important decision. To have the added peace of mind knowing that a high-performance roof system was professionally installed by an authorized contractor and that it is backed by one of the roofing industry's best warranties makes that decision easier.

Through the UNIGUARD™ Warranty Program, UNIFLEX offers both material and total system warranties for many of the different fluid applied roofing system installations. As a business unit of The Sherwin-Williams Company, UNIFLEX systems are backed by a multi-billion-dollar organization.



5/10/15 Year UNIGUARD™ Materials Warranty

UNIGUARD™ materials warranties are recommended for roofs where basic preventative maintenance is needed and where the existing roof condition is sound with few leak issues. UNIFLEX materials-warranted systems are installed by a UNIFLEX Authorized Contractor per required application specifications.



10/15 Year UNIGUARD™ Systems Warranty

UNIGUARD™ 10 and 15-year systems warranties provide comprehensive protection and coverage for a professionally installed UNIFLEX Fluid Applied Roofing system. A full line of coatings, flashing materials, seam tapes, reinforcing fabrics, sealants, and other UNIFLEX branded products are used in these installations, creating a completely watertight and fully enveloped roof system.



1-888-321-3539 or visit uniflexroof.com.

101 PROSPECT AVE NW, CLEVELAND, OHIO 44115



UNIFLEX®
Fluid Applied Roofing Systems

PATCH & REPAIR
ACCESSORIES





UNIFLEX Skylight Restoration Coating

- Provides a protective coating over fiberglass skylight panels
- Restores panel to original condition
- Increases light translucent value

PART NUMBER	SALES NUMBER	COLOR/SIZE
KST01900-20	009920984	Clear 5 Gal.



Fiberglass skylight BEFORE

Raised fiberglass hairs indicate age. Restore with UNIFLEX Skylight Restoration Coating.



PRESSURE WASH fiberglass to remove raised fiberglass hairs and clean the surface.



AFTER pressure washing, notice raised fiberglass hairs are washed off.



STEP 2

APPLY UNIFLEX Skylight Restoration Coating to fiberglass skylight to improve light reflectance below deck.



Coating will remain milky in color for up to 3 days and will dry high-sheen clear.



AFTER

Fiberglass skylight AFTER


Fiberglass is now restored with UNIFLEX Skylight Restoration Coating.



UNIFLEX Acrylic Patching Cement

- Provides a long-lasting, UV and water-resistant patch
- Used to repair roof seams, small holes, splits, cracks, penetrations, and wall flashings on metal, BUR, modified bitumen, polyurethane foam, and concrete roofs

PART NUMBER	SALES NUMBER	COLOR/SIZE
KST041220-20	009921149	White 5 Gal.
KST041220-17	650467673	White 2 Gal.



Fleece Backed Butyl Tape

- Self-adhering, butyl rubber waterproofing tape
- Maintains its flexibility necessary to respond to dynamics of roof movement
- Seals seams, flashing, penetration areas, etc

PART NUMBER	SALES NUMBER	SIZE/PER CASE
KST020802-99	009921073	2" x 50'/12
KST020804-99	009921081	4" x 50'/6
KST020806-99	009921099	6" x 50'/4
KST020808-99	001556554	8" x 50'/3



Typical uses around penetration areas, vertical and horizontal laps, flashing, etc.




Tape should be fully coated after being installed.



UNIFLEX MS Hybrid Roof Bonding Tape-Fleece Backed

- Creates immediate adhesion to roof substrate even underwater
- Applies and adheres to wet surface 0°F and maintains its thermal stability up to 300°F
- Does not need to be coated over



UNIFLEX Polyester Fabric

- Exceptionally strong material
- Accommodates expansion and contraction
- Use for reinforcement for all general roof repairs, seams, flashings, penetration areas and other roof detail areas

PART NUMBER	SALES NUMBER	SIZE/PER CASE
KST20385A-99	009921339	6" x 324'/1
KST20385B-99	650201742	12" x 324'/1
KST20385-99	009920992	40" x 324'/1



Accommodates expansion and contraction.



Use for reinforcement for all general roof repairs and detail roof areas.

PART NUMBER	SALES NUMBER	SIZE/PER CASE
KST058004-99	650433378	4" x 50'/6
KST058006-99	650433386	6" x 50'/4



UNIFLEX Slope Builder

- Slurry coating designed for building up lower lying areas on flat and low slope roof systems
- Protective waterproofing solution
- Just add water; easy to mix

PART NUMBER	SALES NUMBER	COLOR/SIZE
KSTOSLPBD-51	650391311	Gray 5 Gal.

PRODUCT THICKNESS	WEIGHT PER SQ. FT.	COVERAGE RATE PER BATCH
1/16"	.7 lbs.	68 sq. ft.
1/8"	1.4 lbs.	34 sq. ft.
3/16"	2.1 lbs.	22.6 sq. ft.
1/4"	2.8 lbs.	17 sq. ft.
1/2"	5.6 lbs.	8.5 sq. ft.
3/4"	8.4 lbs.	5.6 sq. ft.
1"	11.2 lbs.	4.25 sq. ft.
1-1/2"	16.8 lbs.	2.8 sq. ft.
2"	22.4 lbs.	2.125 sq. ft.



Area of ponding water at HVAC curb.



ADD water and MIX thoroughly.



WASH area to clean surface.



APPLY UNIFLEX Slope Builder to low-lying area and trowel, broom, or squeegee into place.



Make sure area is completely dry.



Once, UNIFLEX Slope Builder is cured, coat over.