



SPF FAQ's

Uniflex SPF FAQ's document is intended to provide a quick view of some frequently asked questions associate with select substrates and installation of Uniflex coatings and SPF.

1. Can I install over TPO? – *Yes. Recovery board needed*
2. Can I install over PVC? – *Yes. Recovery board needed*
3. Can I install it over EPDM? – *Yes. Recovery board needed*
4. Can I install over Mod bit Smooth? - *Yes*
5. Can I install over Mod bit Granulated? – *Yes*
6. Can I install it over Tar and Gravel? – *Yes.*
7. Can I install over Aluminum coated Mod Bit Smooth/Granulated? – *Job specific. Will required additional review by Uniflex and NCFI.*
8. Can I install over Existing SPF coated with acrylic? – *NO. Before the application of the new SPF, you must scarify the existing acrylic coating off when seeking a Uniflex Warranty.*
9. Can I install over Existing SPF coated with silicone? – *NO. Before applying the new SPF, you must scarify the existing silicone coating off when seeking a Uniflex Warranty.*
10. Do I have to scarify sound Existing SPF that has a good coating in place already if I am not seeking a Uniflex Warranty? – *NO, you do not. We acknowledge and respect that as a Roofing Professional at times you will make business decisions that suit your business profile.*
11. Do I have to provide 3rd Party moisture testing on an Existing SPF assembly if I am not seeking a Uniflex Warranty? – *NO, you do not. We acknowledge and respect that as a Roofing Professional at times you will make business decisions that suit your business profile.*

We understand that we cannot answer all questions that may arise on individual projects that you may encounter, we however do encourage all who use Uniflex products to follow good roofing and coatings practices. We encourage you to contact your Uniflex Regional Account Manager for additional support with project questions.

Thank you for your business,

Uniflex



SHERWIN-WILLIAMS.