



# Uniflex Acrylic Snapshot

Single-Ply EPDM, TPO, PVC



<b>P R E P A R E</b>	<b>Conduct:</b>	<b>Moisture Survey &amp; Adhesion Tests</b>
	<b>Repair:</b>	<b>Open Seams, Flashings, Damaged Membrane (Lap Sealant)</b>
	<b>Replace:</b>	<b>Wet Insulation, Pitch Pan Sealants, Termination Sealants</b>
	<b>Clean:</b>	<b>Pressure Wash- EPDM requires Bond-it Wash Primer Uniflex</b>
	<b>Detail:</b>	<b>One Flash</b>
	<b>Apply:</b>	<b>Uniflex SPE Primer 41-321</b>
	<b>Apply:</b>	<b>Uniflex Premium 41-300 Finish-coat</b>

<b>A P P L Y</b>	<b>OneFlash:</b>	<i>Detail all flashings and penetrations. Apply OneFlash at 60 wet mils, extending 2 inches on each side of the overlap seams.</i>
	<b>Basecoat:</b>	<i>Apply Uniflex SPE Acrylic Gray Primer at 1.0 gallons per square. (16 wet mils) to all Field Seams Apply Uniflex SPE Acrylic Gray Primer at 1.5 gallons per square. (24 wet mils) to entire roof surface</i>
	<b>Finishcoat</b>	<i>10 Year System: Apply Uniflex Premium 41-300 at 1.5 gallons per square. (24 wet mils) 15 Year System: Apply Uniflex Premium 41-300 at 2.0 gallons per square. (32 wet mils)</i>

<b>W A R R A N T Y</b>		<b>UNIGUARD™</b> Materials Warranty	<b>Ten or Fifteen Year Available</b>
		<b>UNIGUARD™</b> Systems Warranty	<b>Pre-Approval Required- Warranty Fee Required</b> <b>Ten or Fifteen Year Available</b>

<b>L I N K S</b>	<b>Uniflex Website</b>	<b>P R O D U C T S</b>	<b>Uniflex 41-300 Premium White Finish Coat</b>
	<b>Uniflex Warranty</b>		<b>Uniflex SPE Gray Acrylic Primer</b>
	<b>Full Specification</b>		<b>Uniflex One Flash</b>
	<b>Roof Calculator</b>		<b>Uniflex Bond-it Wash Primer</b>
			<b>Uniflex MS Hybrid Lap Sealant</b>



**Need a Moisture Survey?**

**Ask Your Uniflex Regional Manager about Uniflex Roof View Thermal Imaging or click the image for additional information**

**NOTE:** This Snapshot is not designed to replace the full system specification. Full specifications are available at [www.uniflexroof.com/specifications](http://www.uniflexroof.com/specifications). Contractor must be a Uniflex Approved Applicator for System Warranties.